

## DECLARATION OF PERFORMANCE

### Finnseco KL+ -korjauslaasti repair mortar

No. TIK-A069-2026

1. Unique identification code of the product type: **TIK-A069-2026 Finnseco KL+ - korjauslaasti repair mortar**
2. Intended use: **Product for protection and repair of concrete structures – Structural repair.**
3. Manufacturer: **Tikkurila Oyj, P.O. Box 53, 01301 Vantaa**
4. System of Assessment and Verification of Constancy Performance: **AVCP 4**
5. Harmonised standard: **EN 1504-3:2006**  
Notified body: **Inspecta Sertifiointi Oy**
6. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Compressive strength	Class R3	EN 1504-3:2006
Chloride ion content	< 0,05 %	
Adhesion strength	≥ 1,5 N/mm <sup>2</sup>	
Restricted shrinkage/expansion	NPD	
Resistance to carbonation	NPD	
Modulus of elasticity	NPD	
Capillary uptake	≤ 0,5 kg/(m <sup>2</sup> ·h <sup>0,5</sup> )	
Reaction to fire	A2	
Release of dangerous substances	See SDS	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

A handwritten signature in blue ink, appearing to read 'Magnus Engblom', with a long horizontal flourish extending to the right.

Magnus Engblom  
Portfolio Development Section Leader  
TIKKURILA OYJ

Vantaa 22.05.2026